





48053

american jabos

part 3

PATROL
ORDER
PART




Suggested Kit: Hasegawa P-47 Family




american jabos

part 3


Aircraft 1 "RAID HOT MAMA"
 P-47D-15 RE "RAID HOT MAMA"
 Serial number 276569, 510 FS, 405 FG.
 flown by Lt. JOHN DRUMMOND 1944.
 Camouflage in Olive Drab on top and
 sides of aircraft over Neutral Gray on
 undersides. Windscreen, canopy framing
 and external mirror in dark Blue. Twenty
 four in. cowl, 12" tail stripe and 15"
 stabilizer stripes (located outboard of trim
 tabs) in White. No data block. Early
 Curtiss Electric prop.




Aircraft 2 "THE SCARAB"
 Serial number 276588, 510 ss/ 405 FG.
 flown by Lt. TOM HAMILTON. 1 escort
 mission and 2 sweeps. Olive Drab top and
 sides of aircraft with canopy framing and
 external mirror in Dark Blue. Neutral
 Gray undersides of aircraft. Cowl ring, tail
 strips and stabilizer stripes in White. Nose
 art "THE SCARAB", located on port side
 fuselage.





Aircraft 3 "CHICAGO FAT CAT"
 P-47D-28-RE, 42-28844, "CHICAGO FAT
 CAT", version 2, 510 FS, 405 FG. Pilot
 was Lt. BOB REESE. Natural metal finish
 overall with Red cowl and tail bands. Red
 canopy trim and wing tips. Curtiss Electric
 asymmetric paddle blade propeller with
 Red spinner. Notice Red dot under the
 windshield and rear view mirror.






A/C 1 & 2



A/C 3



References:

-Photos provided by Norris Graser, from the archives and private collections of members of the 405th F.G.

Suggested Kit:

-Hasegawa P-47 Family

Decaling: Apply decals only to a glossy surface.

1. With a sharp scissors or knife, carefully cut item to be used, being careful of not cutting off the clear film around it or that belonging to an adjacent item.
2. Submerge in clean tap water for over 10 seconds and lay over an absorbent paper towel. Decal will slide freely in about 20 seconds. Do not leave decal on water bowl over ten seconds, or adhesive quality will suffer.
3. With a clean brush, apply a setting solution to the area where the decal will finally lay. (Micro, Super or Aero Set will do). With a clean pointed brush slide the decal on to the final area. Allow the setting solution to dry for about 3-5 minutes.
4. With another clean brush, apply a solvent solution over the decal (Micro, Super or Aero Sol will do). Do this if possible in one stroke since your decal will soften up and wrinkle immediately. This is an important step in the process, whatever you do DO NOT TOUCH THE DECAL, after this process until it is totally dry, preferably overnight.
5. When thoroughly dry, rinse your model with tap water and mild soap to wash of excess glue.
6. Finish your model with the desired final coat (gloss, flat, or semi-gloss).



**EAGLE STRIKE
Productions**

**EAGLE STRIKE
Productions**

12982 SW 132nd Ave, Miami, FL, 33186
U.S.A.
Ph: (786) 293-6859, Fax: (786) 293-9286.

Color Schemes



NATURAL METAL NEUTRAL GRAY

RED

OLIVE DRAB

MED. BLUE
F.S. 15180